

AFT/MBS, przyłącze rurowe z gwintem wewnętrznym; jasnoszare (RAL 7035), szare (RAL 7037), czarne (RAL 9005) lub białe (RAL 9010), do łączenia sztywnych lub giętkich rur na skrzynkach rozgałęźnych lub pancernych



Material				Temp.			
PVC-U				-5°C/+60°C *(-25°C/+60°C)			
art	dn	ps	pl	ref			
				jasnoszary light grey	szary* grey*	czarny black	biały white
AFT/MBS 16	16,0	100	2400	020 754	020 783	009 085	010 183
AFT/MBS 20	20,0	100	1200	020 755	020 784	009 086	010 184
AFT/MBS 25	25,0	50	600	020 756	020 785	009 087	010 185
AFT/MBS 32	32,0	20	480	020 757	020 786	009 088	010 186
AFT/MBS 40	40,0	25	300	020 758	020 787	009 089	010 187
AFT/MBS 50	50,0	10	120	020 759	020 788	009 090	010 188

AFT/MBS, adaptor with female thread and male bush; light grey (RAL 7035), grey (RAL 7037), black (RAL 9005) or white (RAL 9010), for the connection of rigid or pliable conduits with distribution and enclosure boxes

AMT/LR, przyłącze rurowe z pierścieniem gwintowanym; jasnoszare (RAL 7035), szare (RAL 7037), czarne (RAL 9005) lub białe (RAL 9010), do łączenia sztywnych i giętkich rur na skrzynkach rozgałęźnych lub pancernych



Material				Temp.			
PVC-U				-5°C/+60°C *(-25°C/+60°C)			
art	dn	ps	pl	ref			
				jasnoszary light grey	szary* grey*	czarny black	biały white
AMT/LR 20	20,0	100	1200	009 574	020 790	009 548	009 600
AMT/LR 25	25,0	50	600	009 575	020 791	009 549	009 601

AMT/LR, adaptor with male thread and lock ring; light grey (RAL 7035), grey (RAL 7037), black (RAL 9005) or white (RAL 9010), for the connection of rigid or pliable conduits with distribution and enclosure boxes

AMT/LN, przyłącze rurowe z nakrętką gwintowaną; jasnoszare (RAL 7035), szare (RAL 7037) lub czarne (RAL 9005), do łączenia sztywnych i giętkich rur na skrzynkach rozgałęźnych lub pancernych



Material				Temp.			
PVC-U				-5°C/+60°C *(-25°C/+60°C)			
art	dn	ps	pl	ref			
				jasnoszary light grey	szary* grey*	czarny black	
AMT/LN 20	20,0	100	1200	009 579	020 792	009 553	
AMT/LN 25	25,0	50	600	009 580	020 793	009 554	

AMT/LN, adaptor with male thread and lock nut; light grey (RAL 7035), grey (RAL 7037) or black (RAL 9005), for the connection of rigid or pliable conduits with distribution and enclosure boxes

MBS, tuleja gwintowana; czarna (RAL 9005) lub biała (RAL 9010)

MBS, male bush; black (RAL 9005) or white (RAL 9010)



Material				Temp.	
PVC-U				-5°C/+60°C	
art	dn	ps	pl	ref	
				czarny black	biały white
MBS 16	16,0	100	2400	009 079	010 189
MBS 20	20,0	100	1200	009 080	010 190
MBS 25	25,0	50	600	009 081	010 191
MBS 32	32,0	20	480	009 082	010 192
MBS 40	40,0	25	300	009 083	010 193
MBS 50	50,0	10	120	009 084	010 194

LR, pierścień gwintowany; czarny (RAL 9005) lub biały (RAL 9010)

LR, lock ring; black (RAL 9005) or white (RAL 9010)



Material				Temp.	
PVC-U				-5°C/+60°C	
art	dn	ps	pl	ref	
				czarny black	biały white
LR 20	20,0	250	10000	009 542	009 594
LR 25	25,0	200	8000	009 543	009 595

LN, nakrętka gwintowana; czarna (RAL 9005) lub biała (RAL 9010)

LN, lock nut; black (RAL 9005) or white (RAL 9010)



Material				Temp.	
PVC-U				-5°C/+60°C	
art	dn	ps	pl	ref	
				czarny black	biały white
LN 16	16,0	200	8000	009 535	009 587
LN 20	20,0	200	8000	009 536	009 588
LN 25	25,0	100	4000	009 537	009 589
LN 32	32,0	100	2400	009 538	009 590
LN 40	40,0	30	1200	009 539	009 591
LN 50	50,0	25	1000	009 540	009 592