

**AK/TW, d lic  p ep zka pro AKU;** b l  (RAL 9010),  
k odd len  jednotliv ch elektrick ch okruh 



materi�l		tepl. rozsah	
PVC		-5�C/+60�C	
typ	mb	vb	ref.�.
AK/TW 100	10	300	000 821
AK/TW 150	10	180	000 822
AK/TW 200	10	100	000 823

**AK/TW, deliaca prep zka pre AKU;** biela (RAL 9010),  
na oddelenie jednotliv ch elektrick ch okruhov

**AK/DS a AK/PLS,  rouby ke kryt m;**  
  2,9mm, d lka 13mm, AK/PLS plombovateln 



typ	mb	ref.�.
AK/DS	100	000 835
AK/PLS	100	000 836

**AK/DS a AK/PLS, skrutky ku krytom;**  
  2,9mm, d lka 13mm, AK/PLS blombovateln 

**AK, velkoprostorov  rozbo n  krabice pod om tku;**  
b l  (RAL 9010), s obrubou a lehce vylomiteln mi otvory  
pro hadice

**Shoda s normami:** IEC/EN 60670



materi�l		tepl. rozsah	
PVC		-5�C/+60�C	
typ	rozm�r [mm]	mb	ref.�.
AK 200/400	200x400x70	5	020 921
AK 200/600	200x600x70	6	020 922
AK 400	400x400x70	4	020 923

**AK, velkopriestorov  rozbo ovacia krabica pod omietku;** biela (RAL 9010), s obrubou a ľahko vylomiteln mi  
otvormi pre ochrann  r rky

**Zhoda s normami:** IEC/EN 60670