

SS, uchwyt rury, z dwoma otworami o montażu;
lakierowany na czarno (RAL 9005) lub cynkowany zanurzeniowo, do montażu śrubami ø 4 mm



lakierowana
lacquered

Material	Temp.
Fe	-45°C/+250°C

art	dn	ps	ref
SS 20 LA	20,0	100	021 069
SS 25 LA	25,0	100	021 070
SS 32 LA	32,0	100	021 071
SS 40 LA	40,0	50	021 072
SS 50 LA	50,0	50	021 073
SS 63 LA	63,0	50	021 074

cynkowana zanurzeniowo
hot dip galvanised



Material	Temp.
Fe	-45°C/+400°C

art	dn	ps	ref
SS 20 FV	20,0	100	021 078
SS 25 FV	25,0	100	021 079
SS 32 FV	32,0	100	021 080
SS 40 FV	40,0	50	021 081
SS 50 FV	50,0	50	021 082
SS 63 FV	63,0	50	021 083

FPE, tuleja końcowa; jasnoszara (RAL 7035) lub czarna (RAL 9005), do ochrony kabli na krawędziach rury



FPE, end cap; light grey (RAL 7035) or black (RAL 9005), for the protection of cables at conduit edges

Material
PVC

art	dn	ps	ref	
			czarny black	jasnoszary light grey
FPE 16	16,0	125	-	061 664
FPE 20	20,0	100	035 425	064 849
FPE 25	25,0	100	035 426	064 850
FPE 32	32,0	50	035 427	064 851
FPE 40	40,0	50	035 428	064 852
FPE 50	50,0	25	035 429	064 853
FPE 63	63,0	10	035 430	064 854