

bezhalogenowe

HFSB, kolanko z przetłoczeniem; jasnoszare (RAL 7035), czarne (RAL 9005) lub białe (RAL 9020), do łączenia sztywnych rur elektroinstalacyjnych pod kątem 90°



Material				Temp.		
PC-Blend				-25°C/+90°C		
art	dn	ps	pl	ref		
				jasnoszary light grey	czarny black	biały white
HFSB 16	16,0	50	600	065 492	009 622	038 576
HFSB 20	20,0	25	300	065 493	009 623	038 577
HFSB 25	25,0	20	160	065 494	009 624	038 578
HFSB 32	32,0	1	50	065 495	009 625	038 579
HFSB 40	40,0	1	35	065 496	009 626	038 580
HFSB 50	50,0	1	20	065 497	009 627	038 581
HFSB 63	63,0	1	8	065 498	-	-

HFSB, normal bend, slip type; light grey (RAL 7035), black (RAL 9005) or white (RAL 9010), for the connection of rigid conduits in an angle of 90°

bezhalogenowe

HFS, uchwyt, z 2 otworami do mocowania; jasnoszary (RAL 7035), czarny (RAL 9005) lub biały (RAL 9010), do montażu śrubami ø 4 mm



Material				Temp.		
PC-Blend				-25°C/+90°C		
art	dn	ps	pl	ref		
				jasnoszary light grey	czarny black	biały white
HFS 16	16,0	100	3200	080 811	020 832	041 831
HFS 20	20,0	100	2400	080 812	020 833	041 832
HFS 25	25,0	100	1600	080 813	020 834	041 833
HFS 32	32,0	100	800	080 814	020 835	041 834
HFS 40	40,0	50	400	080 815	020 836	041 835
HFS 50	50,0	50	400	080 816	020 837	041 836
HFS 63	63,0	25	200	080 817	020 838	-

HFS, saddle, with two fixing holes; light grey (RAL 7035), black (RAL 9005) or white (RAL 9010), for mounting with screws Ø 4mm

bezhalogenowe

HFSBS, uchwyt dystansowy; czarny (RAL 9005)



Material				Temp.		
PC-Blend				-25°C/+90°C		
art	dn	ps	pl	ref		
				czarny black	biały white	
HFSBS 16	16,0	100	2400	009 628	041 852	
HFSBS 20	20,0	50	1200	009 629	037 033	
HFSBS 25	25,0	50	1200	009 630	041 621	
HFSBS 32	32,0	50	600	009 631	041 853	
HFSBS 40	40,0	25	300	009 632	041 854	
HFSBS 50	50,0	25	200	009 633	041 855	

HFSBS, spacer bar saddle; black (RAL 9005)