

Oslony giętkie, bezhalogenowe, z materiału syntetycznego

Flexible Protective Conduits, Halogenfree Synthetic Material

MFXE, giętka karbowana osłona z polietylenu;
czarna (RAL 9005, UV-odporna), w zwojach po 100 m

MFXE, flexible protective conduit from polyethylene,
light gauge, corrugated; black (RAL 9005, UV stabilised), in coils
of 100m



Material	Code	Mechan.	UV stabil.	Temp.
PE	-	> 320 N	☒	-40°C/+100°C
art	dn	di	ps [m]	ref
MFXE 1	7,0	5,2	100	026 328
MFXE 2	9,8	7,2	100	026 329
MFXE 3	11,4	8,5	100	026 330

MFXP, giętka karbowana osłona z polipropylenu;
czarna (RAL 9005, UV - odporna), w zwojach po 100 m

MFXP, flexible protective conduit from polypropylene,
light gauge, corrugated; black (RAL 9005, UV stabilised), in coils
of 100m



Material	Code	Mechan.	UV stabil.	Temp.
PP	-	> 320 N	☒	-40°C/+130°C
art	dn	di	ps [m]	ref
MFXP 1	7,0	5,2	100	035 505
MFXP 2	9,8	7,2	100	035 506
MFXP 3	11,4	8,5	100	035 507